



THERMOFLAN

PTL C6060

- Work area from 180 x 180 mm to 600x600 mm.
- Class 1 workstation with automatic front door.
- Sealed-off CO2 laser source without maintenance.
- Ideal Laser system for cutting and engraving cardboard, paper, leather, wood, acrylic, etc



APPLICATIONS



Paper/Cardboard



Fabrics



Leather



Anodized Metal



Wood



Stone



Fabrics



Signage



Anodized Metal



Glass

www.thermoflan.com

Toute l'information dans le catalogue peut faire l'objet de changements sans préavis.

259 Chemin de la Côte - 30120 MOLIERES-CAVAILLAC (France)
Tél : +33 4 67 81 14 41 - Fax : +33 4 67 81 09 80 - Email: info@thermoflan.com



THERMOFLAN

MODELS:	C6060 80W	C6060 150W	C6060 230W
ENGRAVING HEAD			
Laser Power:	80W	150W	230W
Laser Source:	Sealed-off CO2 laser source.		
Work area (mm):	600x600mm.		
Wavelength:	10,6 µm.		
Engraving speed:	>50,8 cm/s.		
Spot Diameter:	150µm, with work area = 180x180mm 400µm, with work area = 600x600mm		
SYSTEM			
Fume Extraction System:	Need an external extraction system (Not included).		
Cooling System:	Water-cooled (Chiller Included)		
Operating Temperature:	15±35 °C.		
Relative Humidity:	10±85% RH max, non-condensing.		
MTBM:	20.000 hours.		
Preview:	Laser diodes 650 nm 2mW		
Standard Laser Safety:	CLASS 1 Laser system, CEI EN 60825-1		
Dimensions:	1250mm x 2200mm x 1060mm (Width x Height x Depth.)		
INTERFACE			
Control:	DSP microprocessor, Ethernet 10/100 Mbit/s.		
Software:	SW ICARO for Windows environment.		
File Type:	PLT, DXF, BMP, PCX, TIFF, JPEG, GIF MCL, etc.		

OPTIONS



Fume Extraction System
(With Filters)



Fume Extraction System
(Without Filters)

www.thermoflan.com

Toute l'information dans le catalogue peut faire l'objet de changements sans préavis.

259 Chemin de la Côte - 30120 MOLIÈRES-CAVAILLAC (France)
Tél : +33 4 67 81 14 41 - Fax : +33 4 67 81 09 80 - Email: info@thermoflan.com